

D185PDZ

TIER 4 FINAL \ DEUTZ ENGINE \ PORTABLE COMPRESSOR



185CFM/100PSI



SPECIFICATIONS

Compressor

Model	D185PDZ
Rated Delivery	185 CFM (5.2 m ³/min)
Rated Operating Pressure	100 psig (6.9 Bar)
Operating Pressure Range	70-125 psig (4.9 - 8.6 Bar)
Estimated Weight, Serviced	2,340 lbs
Dimensions L x W x H (in")	134" x 55" x 70"

Engine

Туре	Diesel
Make & Model	DEUTZ D2.9L4 Tier 4 Final
Idle Speed	1750 RPM
Fuel Tank Capacity	30 gal (113.5 L)
Horsepower @ rated RPM	49 hp
Full Load Speed	2600 RPM



108mm Air End, designed and made in Michigan City, IN



Easy Access fuel filter, oil filter and dipstick



DEUTZ DOC, Diesel Oxidation Catalyst; allows for maintenance free operation



Sullivan-Palatek Electronic Controller (SPEC)

FEATURES

- » 108mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter -External Access
- » Multiple Service Connections
- » Oil Level Sight Gauge
- » Side by Side Coolers for Compressor and Engine
- » Cooler Access Panel for Cleaning
- » Steel Fuel Tank
- » Safety Chains
- » 15" Wheels & Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Full Length Tool Boxes in Each Side with Lockable Handles
- » Galvaneal Enclosure
- » Galvanized Wheel Wells and Internal Panels
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and **Protection System**
- » Automatic Blowdown Valve
- » Unloaded Starting

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- » Compressor temperature
- » Discharge pressure
- » Engine oil pressure
- » Engine temperature
- » Voltmeter
- » Tachometer
- » Fuel level low fuel warning and shutdown
- » Complete engine diagnostic tool
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet

Sullivan-Palatek, Inc.



219.874.2497



🗯 sullivan-palatek.com 🛮 🖄 info@palatek.com

