


D210UHJD4PTOW

TIER 4 FINAL \ JOHN DEERE ENGINE \ UTILITY MOUNT COMPRESSOR



210CFM/100PSI & 150PSI



SPECIFICATIONS

Compressor

Model	D210UHJD4PTOW
Rated Delivery	210 CFM (5.9 m ³/min)
Rated Operating Pressure	100 psig (6.9 bar) & 150 psig (10.4 Bar)
Operating Pressure Range	70-165 psig (4.9 - 11.3 Bar)
Estimated Weight, Serviced	2,550 lbs (1,157 kg)
Dimensions L x W x H (in")	80" x 35" x 57.31"

Engine

Туре	Diesel
Make & Model	John Deere 4045TFCO3A, B Tier 4 Final
Idle Speed	1600 RPM
Fuel Tank Capacity	25 gal (94.6 L)
Horsepower @ rated RPM	74 hp (55.5 kW)
Full Load Speed	2500 RPM


FEATURES

- 1. Engine Air Filter
- Curbside Fuel Fill 2.
- 3. Compressor Air Filter
- 4. Compressor Oil Filter
- 5. Extended Dipstick
- 6. Fuel/Water Separator
- 7. Engine Oil Filter
- 8. Primary Fuel Filter



SPEC CONTROLLER -

- » Digital readouts
- » Complete engine diagnostic tool
- » Measurement converter
- » Multilingual capabilities
- » Waterproof up to six feet



FEATURES

- » Utility Mount Air Compressor
- **Curbside Controls**
- » Large, 108mm Diameter Twin Screw Air End
- Exclusive Three Year Air End Warranty
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter -External Access
- » High-Low Selector Switch (PTO must be used in low pressure)
- » Two 3/4" Service Connections
- » Oil Level Sight Gauge
- » John Deere Engine
- » Steel Fuel Tank
- » Side by Side Coolers for Compressor and Engine
- » Compact Size for Truck Mounting
- » Curbside Fuel Fill & Air Filter Access
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » All Drains End Mounted
- Automatic Shutdown and **Protection System**
- » Automatic Blowdown Valve
- » Unloaded Starting
- » A Flange PTO (100 psi) B Flange PTO Optional

CONTROLLER

- » Sullivan-Palatek Electronic Controller (SPEC)
 - **Digital Readouts:**
- Compressor temperature
- Discharge Pressure
- Engine oil pressure
- Engine temperature
- Voltmeter
- » Tachometer
- » Fuel level low fuel warning and shutdown
- » Complete engine diagnostic tool
- Unit converter
- Multilingual capabilities
- » Waterproof up to six feet

Sullivan-Palatek, Inc.



219.874.2497



🗯 sullivan-palatek.com 🛮 🖄 info@palatek.com

