



# DC185P31Z-C

EXPORT \ TIER 4 INTERIM \ ISUZU ENGINE \ PORTABLE COMPRESSOR



185CFM/100PSI

# SPECIFICATIONS

## Compressor

Model	DC185P3IZ-C
Rated Delivery	185 CFM (5.2 m <sup>3</sup> /min)
Rated Operating Pressure	100 psig (6.9 Bar)
Operating Pressure Range	70-125 psig (4.9 - 8.6 Bar)
Estimated Weight, Serviced	1,900 lbs
Dimensions L x W x H (in")	122" x 55" x 62"

## Engine

Type	Diesel
Make & Model	ISUZU 4LE1 Tier 4 Interim
Idle Speed	1650 RPM
Fuel Tank Capacity	20 gal (75.7 L)
Horsepower @ rated RPM	48 hp
Full Load Speed	2600 RPM



## FEATURES

- » Large, 108 mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter
- » Multiple Service Connections
- » Oil Level Sight Glass
- » Side by Side Coolers for Compressor and Engine
- » 21 Gallon Fuel Tank
- » Safety Chains
- » 13" Wheels & Tires
- » Choice of Adjustable Height Lunette Eye or Optional Ball Hitch on Drawbar
- » Noise Level Limited to Maximum of 76dBA at 7 Meters
- » Gull-Wing Doors for Superior access to Components and servicing
- » Heavy Duty Lifting Eye
- » Automatic Shutdown and Protection System
- » Automatic Blowdown Valve
- » Stop, Turn, Tail Lights
- » Unloaded Starting
- » Standard Instrumentation
  - » Alternator Light
  - » Discharge Pressure Gauge
  - » Hourmeter

**Sullivan-Palatek, Inc.**

1201 West US Highway 20  
Michigan City, IN 46360

219.874.2497

sullivan-palatek.com

info@palatek.com