



Sullivan
Palatek

C-SERIES, C-15\20\25\30

15-30 HP \ INTEGRAL DRYERS \ INDUSTRIAL ELECTRIC COMPRESSORS



C-15, 15 HP \ C-20, 20 HP \ C-25, 25 HP \ C-30, 30 HP

Dependable by design.™

SPECIFICATIONS

Model		C-15	C-20	C-25	C-30
Capacity @ 125 PSI	cfm	46	84	110	115
Motor	hp (kW)	15 (11.2)	20 (15)	25 (18.6)	30 (22.4)
Motor Speed	rpm	3500	3540	3555	3555
Sump Capacity	gal (L)	1.6 (6)	1.85 (7)	1.85 (7)	1.85 (7)
Discharge NPT	in	1/2 inch	1/2 inch	1 inch	1 inch
Length	in (mm)	53 (1346)	54.5 (1384)	54.5 (1384)	54.5 (1384)
Width	in (mm)	28 (711)	35 (889)	35 (889)	35 (889)
Height	in (mm)	45 (1143)	49 (1244)	49 (1244)	49 (1244)
Weight	lbs (kg)	970 (440)	1377 (625)	1450 (658)	1500 (680)

*100 psi and 145 psi also available

All data provided is based on preliminary testing and could change without notice



» Pictured above: C-25 with integral dryer package.

FEATURES

- » Energy efficient
- » Quiet - 68dba
- » TEFC motor
- » 208/230/460/ 3/60
- » 230/1/60
- » Microprocessor control
- » Multi point measuring and protection of pressure and temperature
- » RS-485 communication interface function
- » Seven function maintenance schedule/ monitoring
- » Full function electrical control for motor protection
 - » Motor overload relay
 - » Phase protection



Displays:

- » Run time
- » Load time
- » Oil filter change time
- » Separator change time
- » Oil change time
- » High temperature alarm
- » Overload alarm
- » RS 485 Communication

Sullivan-Palatek, Inc.

1201 West US Highway 20
Michigan City, IN 46360

219.874.2497

sullivan-palatek.com

info@palatek.com