



1150CFM SERIES

TIER 4 FINAL \ PORTABLE COMPRESSOR \ DUAL CAPACITY \ VARIABLE PRESSURE



1150CFM/350PSI 900CFM/500PSI



Dependable by design.™

SPECIFICATIONS

Compressor

Model
Rated Delivery @ Rated Pressure
Operating Pressure Range
Estimated Weight, Serviced
Dimensions L x W x H (in")

Engine

Model	D1150PXHD1CU4
Make & Model	CUMMINS QSX 15 Tier 4 Final
Idle Speed	1400 RPM
Fuel Tank Capacity	224 gal (848 L)
Horsepower @ rated RPM	535 hp (399 kW)
Full Load Speed	1900 RPM
DEF Volume	15 gal. (56.7 L)





Pressure Selection Screen

Sullivan-Palatek, Inc.

219.874.2497

sullivan-palatek.com 🖄 info@palatek.com

FEATURES

- Two Stage 20/12 Air End »
- Dual Pressure 350/500 psi »
- » Air End Manufactured by Sullivan-Palatek, Comes With Exclusive Two Year Warranty
- » 8" Closed Start, Inlet Valve
- » 3" Service Connection
- **Oil Level Sight Gauge** »
- **Cummins Engines** »
- Steel Fuel Tank (TC Certified) »
- Four Point Lifting Bail »
- Dual Axle Running Gear it » »
 - **Electric Brakes**
- » Adjustable 3" Lunette Eye
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » Automatic Shutdown and **Protection System**
- » Containment Base
- » Large Service Doors for Easy Maintenance
- » Automatic Blowdown Valve
- Dual Air Outlets (with After-» cooler option)
- Options »
 - » Built in Aftercooler and Filters for instrument quality air

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- Compressor temperature »
- **Discharge Pressure** »
- Engine oil pressure »
- Engine Coolant temperature »
- Voltmeter »
- Tachometer »
- Fuel level low fuel warning » and shutdown
- Complete engine diagnostic » tool
- Unit converter »
- Multilingual capabilities »
- » Waterproof IP66/67
- **Air Filter Service** »
- After cooler filter warning »

Sullivan-Palatek Electronic

D

Controller (SPEC)

D1150PXHD1CU4

25.5 m3/min @ 34.5 bar - 32.6 m3/min @ 24.2 bar

900 CFM @ 500 psi - 1150 CFM @ 350 psi

270 psi (18.6 bar) - 500 psi (34.5 bar)



19,500 lbs 254.31" x 90.15" x 111.82"