



D375PHKR

TIER 4 FINAL \ KOHLER ENGINE \ PORTABLE COMPRESSOR \ VARIABLE PRESSURE



375CFM/150PSI



SPECIFICATIONS

Compressor

Model	D375PHKR
Rated Delivery	375 CFM (10.6 m ³ /min)
Rated Operating Pressure	150 psig (10.4 Bar)
Operating Pressure Range	70-170 psig (4.9 - 11.72 Bar)
Estimated Weight, Serviced	5,000 lbs
Dimensions L x W x H - in" (w/o Running Gear L x W x H)	151" x 79" x 77.5" (101" x 56.5" x 53.5")

Engine

Туре	Diesel
Make & Model	KOHLER TIER 4 FINAL KDI3404
Idle Speed	1600 RPM
Fuel Tank Capacity	60 gal (227 L)
Horsepower @ rated RPM	134 hp (99.9 kW)
Full Load Speed	2200 RPM
DEF Tank*	4.2 gal (16 L)

^{*}DEF Fluid Required



Sullivan-Palatek Electronic **Controller (SPEC)**

FEATURES

- » Large, 130mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty on Air End, Unlimited Hours
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter with Indicators
- » Oil Level Sight Gauge
- » Choice of Lunette Eye or Ball Hitch on Height Adjustable Drawbar
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » Galvanneal Enclosure-Rust & **Corrosion Resistant**
- » Automatic Safety Shutdown
 - High Compressor Discharge Temperature
 - · High Engine Temperature
 - · Low Engine Oil Pressure
- » Full Containment Frame
- » Remote Drains
- » Automatic Blowdown Valve
- » LED Stop, Turn, Tail Lights
- » Unloaded Starting
- » E-Stop
- » Completely contained filtration
- » Separate dual outlets for instrument quality air internal lock out
 - 1-1½" NPT
 - 1 3/4" NPT

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- » Compressor Temperature
- » Discharge Pressure
- » Engine Coolant Temperature
- » Voltmeter
- » Tachometer
- » Fuel Level Low Fuel Warning and Shutdown
- » Complete Engine Diagnostic Tool
- » Waterproof IP66/67
- » Air Filter Service
- » Aftercooler Filter Warning
- » Measurement converter

Sullivan-Palatek, Inc.



219.874.2497



sullivan-palatek.com 🙎 info@palatek.com

