



# D185PIZ4

TIER 4 FINAL \ ISUZU ENGINE \ PORTABLE COMPRESSOR



### 185CFM/100PSI



Dependable by design.<sup>™</sup>

## **SPECIFICATIONS**

#### Compressor

Model	D185PIZ4
Rated Delivery	185 CFM (5.2 m <sup>3</sup> /min)
Rated Operating Pressure	100 psig (6.9 Bar)
Operating Pressure Range	70-125 psig (4.9 - 8.6 Bar)
Estimated Weight, Serviced	2,340 lbs
Dimensions L x W x H (in")	134" x 55" x 70"

#### Engine

Туре	Diesel
Make & Model	ISUZU 4LE2T Tier 4 Final
Idle Speed	1400 RPM
Fuel Tank Capacity	30 gal (113.5 L)
Horsepower @ rated RPM	49 hp @ 2400 RPM
Full Load Speed	2400 RPM



Sullivan-Palatek Electronic Controller (SPEC)

#### FEATURES

- » 108mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter -External Access
- » Multiple Service Connections
- » Oil Level Sight Gauge
- » Side by Side Coolers for Compressor and Engine
- » Cooler Access Panel for Cleaning
- » Steel Fuel Tank
- » Safety Chains
- » 15" Wheels & Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Full Length Tool Boxes in Each Side with Lockable Handles
- » Galvaneal Enclosure
- » Galvanized Wheel Wells and **Internal Panels**
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and Protection System
- » Automatic Blowdown Valve
- » Unloaded Starting

#### CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC) **Digital Readouts:** 

- » Compressor temperature
- Engine oil pressure »
- Engine temperature »
- Voltmeter
- Tachometer
- » Fuel level low fuel warning and shutdown
- » Complete engine diagnostic tool
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet

Sullivan-Palatek, Inc.

219.874.2497

🗰 sullivan-palatek.com 🛛 🖄 info@palatek.com