



# D260PDKR

DUAL PRESSURE \ DUAL CAPACITY \ TIER 4 FINAL \ KOHLER ENGINE \ PORTABLE COMPRESSOR



## 260CFM/100PSI 185CFM/150PSI



Dependable by design.<sup>™</sup>

# **SPECIFICATIONS**

#### Compressor

Model	D260PDKR
Rated Delivery @ Rated Pressure	260 CFM @ 100 psi - 185 CFM @ 150 psi 7.4 m3/min @ 6.9 bar - 5.2 m3/min @ 10.4 bar
Operating Pressure Range	70 psi (4.8 bar) - 180 psi (12 bar)
Estimated Weight, Serviced	2,500 lbs
Dimensions L x W x H (in")	134" x 55" x 72"

#### Engine

Туре	Diesel
Make & Model	KOHLER 2504 Tier 4 Final
Idle Speed	1650 RPM
Fuel Tank Capacity	30 gal (109.8 L)
Horsepower @ rated RPM	74 hp
Full Load Speed	2400 RPM @ 260 CFM 1900 RM @ 185 CFM



## Sullivan-Palatek, Inc.

219.874.2497

🗰 sullivan-palatek.com 🛛 🖄 info@palatek.com

#### FEATURES

- » 127mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- Automatic 0 to 100% Capacity Control
- Two Stage Dry Type Air Filter with Safety Elements - External Access
- **Multiple Service Connections**
- Oil Level Sight Gauge
- Side by Side Coolers for Compressor and Engine » KOHLER 2504 Tier 4 Engine
- » Steel Fuel Tank
- » Cooler Access Panel for Cleaning
- » Safety Chains
- » 15" Wheels & Radial Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Tool Boxes in Each Side with Lockable Handles » Galvanneal Enclosure
- » Galvanized Wheel Wells and **Internal Panels**
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and **Protection System**
- » Automatic Blowdown Valve
- » Stop, Turn and Tail Lights
- » Unloaded Starting
- » High-Low Selector Valve

### **.CONTROLLER**

Sullivan-Palatek Electronic Controller (SPEC) Digital Readouts:

- » Compressor temperature
- » Discharge pressure
- Engine oil pressure »
- » Engine Coolant temperature
- » Voltmeter
- Tachometer »
- » Fuel level low fuel warning and shutdown
- » Fault Codes
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet