Portable Rotary Compressor MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: SULLIVAN-PALATEK		Sullivan Palatek
	Model Number: D750PH5CU5	Date:	12/4/2023
2	X Oil-injected Oil-free	Fuel Type: # of compression Stages:	Diesel 1
3	Rated Capacity at Full Load Operating Pressure <sup>a, d</sup>	750	acfm
4	Nominal Engine speed (reference only)	1900	rpm
5	Full Load Operating Pressure <sup>b</sup>	150	psig
6	Maximum Full Flow Operating Pressure <sup>c</sup>	150	psig
7	Engine Nominal HP Rating	310	hp
8	Engine Mfg. / Emission Compliance Level	CUMMINS	Tier 4 Stage V
9	Fuel Consumption at Full Load <sup>e</sup>	14	gallons per hour

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex D; ACFM is actual cubic feet per minute at inlet conditions.

b. The operating pressure at which the Capacity (Item 3) was measured for this data sheet.

Member

c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.

d. Tolerance is specified in ISO 1217, Annex Ď, as shown in table below: e. Read from control panel.



Volume Flow Rate Specified Fuel Consumption Volume Flow Rate at specified conditions % %  $\underline{m^3} / \underline{min}$ ft<sup>3</sup> / min Below 17.6 Below 0.5 +/- 7 +/- 8 0.5 to 1.5 +/- 6 +/- 7 17.6 to 53 1.5 to 15 +/- 5 +/- 6 53 to 529.7 +/- 4 +/- 5 Above 15 Above 529.7

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.