| Portable Rotary Compressor MODEL DATA - FOR COMPRESSED AIR | | | |
|---|--|-----------------------------|---------------------|
| 1 | Manufacturer: SULLIVAN-PALATER | | Sullivan Palatek |
| 2 | Model Number: D260UHJD5 | Date: | 12/4/2023 |
| | | Fuel Type: | Diesel |
| | X Oil-injected Oil-free | # of compression Stages: | 1 |
| 3 | Rated Capacity at Full Load Operating Pressure ^{a, d} | 260 | acfm |
| 4 | Nominal Engine speed (reference only) | 2500 | rpm |
| 5 | Full Load Operating Pressure ^b | 100 | psig |
| 6 | Maximum Full Flow Operating Pressure ^c | 100 | psig |
| 7 | Engine Nominal HP Rating | 74 | hp |
| 8 | Engine Mfg. / Emission Compliance Level | JOHN DEERE | Tier 4 Stage V |
| 9 | Fuel Consumption at Full Load ^e | 4.8 | gallons per hour |

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex D; ACFM is actual cubic feet per minute at inlet conditions.

b. The operating pressure at which the Capacity (Item 3) was measured for this data sheet.

Member

c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.

d. Tolerance is specified in ISO 1217, Annex D, as shown in table below: e. Read from control panel.



Volume Flow Rate Specified Fuel Consumption Volume Flow Rate at specified conditions % % $\underline{m^3} / \underline{min}$ ft³ / min Below 17.6 Below 0.5 +/- 8 +/- 7 0.5 to 1.5 +/- 6 +/- 7 17.6 to 53 1.5 to 15 +/- 5 +/- 6 53 to 529.7 +/- 4 +/- 5 Above 15 Above 529.7

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.