



DR750-10TCA

TIER 3 \ SINGLE AXLE \ CATERPILLAR ENGINE \ PORTABLE COMPRESSOR



750CFM/150PSI

SPECIFICATIONS

Compressor

Model	DR750-10TCA
Rated Delivery	750 CFM (21.2 m ³ /min)
Rated Operating Pressure	150 psig (10.4 Bar)
Operating Pressure Range	70-150 psig (4.9 - 10.4 Bar)
Estimated Weight, Serviced	7,716 lbs (3,500 kg)
Dimensions L x W x H (in")	210" x 81.4" x 87.3"

Engine

Model	Diesel
Make & Model	CATERPILLAR C7 TIER 3
Idle Speed	1450 RPM
Fuel Tank Capacity	119 gal (450 L)
Horsepower @ rated RPM	270 hp (203 kW)
Full Load Speed	1800 RPM



FEATURES

- » Caterpillar Engine
- » Energy Efficient Twin Screw Rotor Air Ends for Stable and Continuous Air Supply
- » Air End Manufactured by Sullivan-Palatek Comes With Exclusive Three Year Warranty
- » Highly Flexible Coupling Between Rotors and Engine for Improved Reliability
- » Machine Protection Level - IP23
- » Control Cabinet Protection Level - IP54
- » Forklift Pockets
- » Lifting Bail
- » Draw Bar w/ Single Axle Standard Machine
- » No High Wear Parts, Reducing Cost of Maintenance
- » Energy Efficient Inlet Valve Mechanism
- » Sound Deadening Material Ensures Quiet Operation
- » Air Oil Separator With Wave Shaping Technology Ensures Highest Quality Discharge With No More Than 2PPM Carry Over

CONTROLLER



Sullivan-Palatek, Inc.

1201 West US Highway 20
Michigan City, IN 46360

219.874.2497

sullivan-palatek.com

info@palatek.com