D260PDKR

DUAL PRESSURE \ DUAL CAPACITY \ TIER 4 FINAL \ KOHLER ENGINE \ PORTABLE COMPRESSOR

260CFM/100PSI 220CFM/150PSI

Dependable by design.™

SPECIFICATIONS

Compressor

Model	D260PDKR
Rated Delivery @ Rated Pressure	260 CFM @ 100 psi - 220 CFM @ 150 psi 7.4 m3/min @ 6.9 bar - 5.2 m3/min @ 10.4 bar
Operating Pressure Range	70 psi (4.8 bar) - 180 psi (12 bar)
Estimated Weight, Serviced	2,500 lbs
Dimensions L x W x H (in")	134" x 55" x 72"

Engine

Type	Diesel
Make & Model	KOHLER 2504 Tier 4 Final
Idle Speed	1650 RPM
Fuel Tank Capacity	30 gal (109.8 L)
Horsepower @ rated RPM	74 hp
Full Load Speed	2400 RPM @ 260 CFM 1900 RM @ 220 CFM

FEATURES

- 127mm Diameter Twin Screw Air End
- Exclusive Three Year Warranty On Air End
- Automatic 0 to 100% Capacity Control
- Two Stage Dry Type Air Filter with Safety Elements - External Access
- Multiple Service Connections
- Oil Level Sight Gauge
- Side by Side Coolers for Compressor and Engine
- KOHLER 2504 Tier 4 Engine
- Steel Fuel Tank
- Cooler Access Panel for Cleaning
- Safety Chains
- 15" Wheels & Radial Tires
- Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- Large Tool Boxes in Each Side with Lockable Handles
- Galvanneal Enclosure
- Galvanized Wheel Wells and Internal Panels
- Easily Removable Upper Enclosure
- Automatic Shutdown and Protection System
- Automatic Blowdown Valve
- Stop, Turn and Tail Lights
- Unloaded Starting
- High-Low Selector Valve

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- Compressor temperature
- Discharge pressure
- Engine oil pressure
- Engine Coolant temperature
- Voltmeter
- Tachometer
- Fuel level - low fuel warning and shutdown
- Fault Codes
- Unit converter
- Multilingual capabilities
- Waterproof up to six feet

Sullivan-Palatek, Inc.
1201 West US Highway 20
Michigan City, IN 46360

219.874.2497 sullivan-palatek.com info@palatek.com

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

05018731-0005 R03