



750-900CFM CU-SERIES

TIER 4 FINAL - STAGE V \ CUMMINS ENGINE \ PORTABLE COMPRESSOR \ VARIABLE PRESSURE



750CFM / 100/150PSI 900CFM / 100/150PSI



SPECIFICATIONS

Compressor	
Туре	Single Stage, oil flooded rotary screw
Ambient Oper. Temp. Range	-40° to + 125°F (-40° to +52°C)
Oil Capacity	42 gal. (114 L)
Air Service Connections	2" NPT
Operating Pressure Range	90-150 psig (6.2 - 10.3 Bar)
Estimated Weight, Serviced	11,500 lbs
Dimensions L x W x H (in")	215.2" x 76.6" x 96.62"

Engine

Туре	Diesel
Make & Model	CUMMINS QSB6.7 Tier 4 Final - Stage V
Idle Speed	1400 RPM
Fuel Tank Capacity	150 gal (568 L)
Horsepower @ rated RPM	310 hp (231 kW)
Full Load Speed	1900 RPM
DEF Volume	15 gal (56.8 L)

Models

Model	Rated Delivery	Rated Operating Pressure
D750PH5CU5	750 cfm (21.2 m ³/min)	100/150 psig (6.9/10.4 Bar)
D900PH5CU5	900 cfm (26.4 m ³/min)	100/150 psig (6.9/10.4 Bar)

Sullivan-Palatek Electronic Controller (SPEC)



FEATURES

- » Large 204mm Diameter Twin Screw Air End Manufactured In The USA by Sullivan-Palatek
- Three Year Unlimited Hour Air **End Warranty**
- » Automatic 0 to 100% Capacity Control
- » 2" Service Connection
- Oil Level Sight Gauge
- **Cummins Engine**
- **Aluminized Fuel Tanks**
- Single Point Lifting Bail
- Dual-Axle Running Gear
- » Adjustable 3" Lunette Eye
- » Automatic Shutdown and **Protection System**
- » Electric Brakes Standard
- » Galvanneal sheet metal
- » Block Heater standard with Cummins Engine
- » E-Z Lube Axle Bearings
- » Containment Base
- » Automatic Blowdown Valve
- » Large Service Doors for ease of Maintenance

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- » Compressor temperature
- » Discharge Pressure
- Engine oil pressure
- Engine Coolant temperature
- Voltmeter
- » Tachometer
- » Fuel level low fuel warning and shutdown
- Complete engine diagnostic
- » Unit converter
- Multilingual capabilities
- Waterproof IP66/67
- » Air Filter Service
- » After cooler filter warning

Sullivan-Palatek, Inc.



219.874.2497





🗯 sullivan-palatek.com 🛮 🖄 info@palatek.com